





## Glancetron GT19open

High-end touch monitor for mounting

- In-counter touch monitor for public areas
- Brilliant presentation on 19" (48.3 cm)
- Stylish: open-frame glass surface
- Durable, thanks to projected capacitive technology
- Generous scope of delivery, optional remote control

### Specifications

Display	Screen diagonal / type	48.3 cm (19") / LCD TFT active matrix
	Aspect ratio	4:3
	Resolution (max.)	1280 x 1024 pixels
	Active area (HxW)	301 x 376 mm
	Response time	5 ms
	Colours	16.7 million
	Contrast	800:1
	Brightness	225 cd/m <sup>2</sup>
	Viewing angle (H/V)	160° / 160°
	Video input	VGA / DVI-D
	Touch technology	Projected capacitive
General	Touch interface	USB (HID)
	Colour	Dark grey
	Dimensions (WxHxD)	432.9 x 360.3 x 55.4 mm
	Weight	5.5 kg / Shipping weight: 8 kg
	Power supply	external power supply (DC 12V; 4.16A)
	Power consumption	Operating: 25 W / Sleep: 3 W / Standby: 1 W
	Mounting options	Open-frame with mounting brackets / VESA (75 x 75 mm / 100 x 100 mm)
	Control buttons	Power on/off, Menu, Select, Up, Down
	Certifications	TUV, CE, UL, CUL, FCC, RoHS
	Drivers	Windows 7, VISTA, XP, 2000, CE, XP Embedded, Linux, Apple® Mac OS
	Options	n/a
Environment	Delivery contents	Monitor, stand, connection cables (USB, VGA, DVI), power cord (EU, UK), cable cover, driver CD, QSG
	Operating temperature	0 to +40 °C
	Storage temperature	-20 to +60 °C
	Operating humidity	20 to 80 % (non-condensing)
	Storage humidity	10 to 90 % (non-condensing)



Your partner